



Prime Coat™

Product Description

VHT® Prime Coat™ is an excellent foundation for any enamel, acrylic or synthetic lacquer. It provides a tough, air-dry base with excellent adhesion to intermediate and top coatings. It is specially formulated to fill scratches or pin holes caused by sanding or body fillers to form a strong corrosion barrier. It is a multi-purpose product.

Product Characteristics

Primer: Self-etching

Color: White, Dark Gray, Red Oxide, Light Gray, Black, and Yellow Zinc Chromate.

Finish: Flat

Properties

Product Weight: 8.3 lb/gal

Flash Point: 16°F PMCC

Coating System

VHT provides a multi-high performance coating system for the ultimate in protection and quality. This system includes surface preparation and Prime Coat.

Prep SP445 Prep Spray

Prime SPxxx Prime Coat

Uses

Automotive, Marine, Aviation, Home, Farm, and Industrial

Surfaces:

- Metal, Fiberglass, Masonry, Wood, and most plastic surfaces.

Application

Prepare the surface by removing loose paint, dirt, rust, grease, wax, etc. Use grease and wax remover to clean surface. Lightly sand surface with a Red Scotch Brite pad or 320-grit sandpaper. Wipe surface down with grease and wax remover again.

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60° F (16° C) and 95° F (35° C) and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. Shake can for 10 seconds after each minute of use. To spray, hold can parallel 8 to 10 inches from the surface to be painted and use an even, sweeping motion. To avoid runs or sags, apply in light coats. Allow surface to dry 10 minutes between each coat and 30 minutes before sanding or applying finished coat of paint.

If needed sanding can be done wet or dry after 30 minutes with 600 grit sandpaper. If scratches are still present repeat step #3 (shake can vigorously...). (Note: product is not recommended for use on damaged areas more than 1/16 inch deep). When primer application is complete, refinish primed area with appropriate VHT paint. Covers approximately 12-14 square feet.

Packaging

Per Case: 6 cans

Case Weight: 5.7 lbs

Cases/Pallet: 315

Units/Pallet: 630 cans